

729-733 Woven Glass Tape

**Technical
Data Sheet**

729-730



General Description

When bonded with epoxy, Episize™ Glass Tape provides additional tensile strength to resist hairline crack development and abrasion. When used by itself, it is particularly suited to reinforcing chines and the corners of hulls or decks, as well as many other similar structural applications. Glass Tape is a versatile, woven fabric tape with bound edges.

- 729A – 175g/m² Plain Weave Glass Tape 25mm wide 10m Length
- 729B – 175g/m² Plain Weave Glass Tape 25mm wide 50m Roll
- 730A – 175g/m² Plain Weave Glass Tape 50mm wide 10m Length
- 730B – 175g/m² Plain Weave Glass Tape 50mm wide 50m Roll
- 731A – 175g/m² Plain Weave Glass Tape 75mm wide 10m Length
- 731B – 175g/m² Plain Weave Glass Tape 75mm wide 50m Roll
- 732A – 175g/m² Plain Weave Glass Tape 100mm wide 10m Length
- 732B – 175g/m² Plain Weave Glass Tape 100mm wide 50m Roll
- 733A – 175g/m² Plain Weave Glass Tape 150mm wide 10m Length
- 733B – 175g/m² Plain Weave Glass Tape 150mm wide 50m Roll

Characteristics

Width	25mm – 150mm
Weight	175g/m ²
Fibre Orientation	0°/90°
Warp	33.6%
Weft	66.4%
Approximate thickness.....	0.17mm
Cured Appearance	Almost Clear
Warp Fibre	EC9 68 TEX
Weft Fibre.....	EC9 68 TEX

West System International
Cupernham House
Cupernham Lane
Romsey, Hampshire
SO51 7LF, UK

+44(0)1794 521111

westsystem.co.uk

ISO9001:2008 Certified

REV 1 / Dec, 2016

These are typical properties and cannot be construed as a specification. The end users should test the products to ensure the products are suitable for the intended application. Any information, data, advice or recommendation published by Wessex Resins by other means and whether relating to Wessex Resins' materials or other materials, is given in good faith and believed to be reliable.